





ST-520MA Stand-alone Waterproof Proximity Access Control







- Waterproof design. Tight structure design of silicone washer. Durable and strong weather resistance.
- Touch proximity panel. With indicator and door bell.
- 8 sets of door open password available to set.
- 1000 cards capacity to use. Customized proximity panel and frame color are available.
- Tricolored BAR and a set of external indicator light (RED) which goes with a set of buzzer to indiate operation. External indicator light is available for user to set.
- Duress code installation. If user is being held as hostage, specific password can be entered and help signal will be dispatched immediately.


Specification DC 12V ±15% Power Supply 150mA (standby); Power consumption 200mA (operation)±5% Door bell control Built-in RELAY(1A@DC 12V) connector Door control RELAY Built-in RELAY(1A@DC 12V) Fireproof polycarbonate material Outer casing 13.56MHz Frequency 1. Password 2. Proximity card Five door opening 3. Proximity card and password methods 4. Password or proximity card 5. Special system password. 00-99 seconds Door closing time 1000 Card capacity 1. Exit push button 2. Anti-theft detection Input point 3. Door sensing input 1. Door open output 2. Alarm output Output point 3.Anti-Duress alarm output Keyboard 3×4, Touch proximity panel Weight 300 g (included wrapping)

Series Mode

ST-520MA:13.56MHz,Mifare format ST-520MAH:13.56MHz,Mifare SOCA format

Dimensions

Unit:mm



Structure Diagram

Unit:mm

