







Series Model

- ST-226: ANSI style, 125KHz EM-Marin format
- ST-228: British style, 125KHz EM-Marin format

Special features

- 8 sets of door opening password available for user to set.
- 1,000 cards capacity.
- Five door opening methods.
- Embedded type of installation to prevent rough surface of the wall which may cause damage to the unit.
- Complete waterproof unit and suitable for outdoor installation.
- Stainless steel durable buttons, anti-acidity and salinity.
- Use with anti-theft unit for setting function.

Specification


- Power Supply: DC 12V ±15%
- Case: stainless steel #304 and PC fireproof material.
- Frequency: 125KHz
- Door closing time: 00-99 seconds
- Card capacity: 1000
- Operation mode: Standalone
- Dimensions:
 - ST-228 : $86L \times 86W \times 30.8H$ (mm). ST-226 : $115L \times 70W \times 30.8H$ (mm).
- Weight: 200g (included wrapping).


- Power consumption: 130mA (standby); 150mA (operation) ±5%
- 8 sets of door open password available to set.
- Five door opening methods:
 - 1. Password
 - 2. Proximity card
 - 3. Proximity card and password
 - 4. Password or proximity card
 - 5. Special system password
- Input point: 1. Exit push button 2. Anti-theft detection
 - 3. Door sensing input 4. LED control(Orange)
- Output point: 1. Door open connector
 2. Alarm output
- Keyboard: 3×4, 12 Stainless steel translucent buttons.

Waterproof

ST-228 ST-226 Water Water Complete waterproof unit

Dimenisions





Structure diagram

